

MODEL	HULL MATERIAL VARIANTS			LENGTH VARIANTS (M)								PROPULSION VARIANTS			MAX. LOAD (KG)		
	COMPOSITE	ALUMINIUM	POLYETHYLENE	13	12	11	10	9	8	7	6	BEAM WIDTH (M)	OUTBOARD	INBOARD STERNDRIVE		INBOARD WATERJET	
SPECIAL OPERATIONS BOATS													MAX SPEED RANGE AT LIGHT LOAD (KN)				
1200	C	A		13	12							3,80	50-60	40-45	35-40	2500	
1100	C	A				11	10					3,50	50-60	40-45	35-40	2000	
950D	C	A					10,5	9,5				3,00	55-60			1800	
950	C	A					10	9,5				3,00	50-60	40-45	35-40	1800	
850	C							8,7	8,5	8,1		2,75	45-50	40-45	30-35	1500	
740	C									7,4		2,85	45-50	40-45	30-35	1200	
PATROL BOATS																	
1200	C	A		13	12							3,80	50-60	40-45	35 - 40	2500	
1100	C	A				11	10					3,50	50-60	40-45	35 - 40	2000	
FAST RESCUE BOATS																	
1000	C	•					10	9,5				3,50	45-50	40-45		2000	
850	C	•						8,7	8,5			2,75		40-45	30-34	1800	
810	C	•							8,1			2,75			30-34	1600	
740	C									7,4		2,85			30-34	1200	
650	C	•									6,5	2,45			30-33	900	
600	C										6	2,45			30-33	850	
WORKBOATS																	
740	C		F							7,4		2,85	O	O	30-35	1200	
680	C	A								6,8	6,5	6	2,45	40-45	35-40	30-35	1000
650	C	A	F							6,5	6,4	6	2,45	40-45	35-40	30-35	900

All illustrations, dimensions and performance values are indicative and subject to project specific requirements.

C = Composite hull

A = Aluminium hull

F = Polyethylene hull

• = Optional, available as special order